



1070 Decade Capacitance Box

Time Electronics
Calibration, Test & Measurement

- 100 pF to 10 μ F
- 1% Accuracy
- In-line read-out
- Colour coded digits
- Bi-polar working
- Safety terminals
- Removable protective boot



High accuracy and wide range makes the **1070** capacitance box suitable for many applications in industry and education. It is housed in a metal case to provide complete screening and a residual capacitance of approximately 40pF.

Safety Terminals: Fully compatible with 4mm shrouded plugs, as well as standard plugs, bare wires, and spade terminals.

Clear Visual Indication: To enhance reading the setting, the 1070 has colour coded digits as shown in the above image; μ F (red), nF (white), and pF (yellow).

Added Protection: The 1070 comes fitted with an ergonomic rubber boot (9028) providing increased protection and durability. The boot has a textured grip for comfortable handling and a raised edge so the 1070 angles slightly upward when resting horizontally. This improves visibility as well as gripping the surface, meaning no movement when thumbwheel switches are pressed. It is easy to remove if the user prefers a stand-alone unit or to house the decade box in the 9026 carry case.

1070 Technical Specifications

RANGE	TYPE	ACCURACY @ 1kHz	MAX VOLTAGE	TEMP COEFF ppm/°C max	POWER FACTOR @ 1kHz	INSULATION RESISTANCE
9 x 100pF	Silver mica	1% \pm 5pF	300V dc 200V ac	200	< 0.0015	> 50G Ω
9 x 1nF	Silver mica	1% \pm 5pF	300V dc 200V ac	50	< 0.002	> 50G Ω
9 x 10nF	Silver mica	1%	100V dc 72V ac	50	< 0.01	> 30G Ω
9 x 100nF	Polycarbonate	1%	100V dc 72V ac	75	< 0.01	> 30G Ω
9 x 1 μ F	Polycarbonate	1%	100V dc 115V ac	75	< 0.01	> 30G Ω

General Specification

Dimensions:	4.5 x 4 x 8" (110 x 75 x 200 mm)
Weight:	1.3lb (0.6kg)
Supplied with:	2 year warranty, test leads, protective rubber boot, factory certificate, and carry case
Optional Extras:	UKAS/NIST Traceable Calibration Certificate

Ordering Information

Code	Description
1070	Decade Capacitance Box
9114	UKAS/NIST Traceable Calibration Certificate