

QSQS-HOS-8ft

Quick-test 6900 psi hose, S.S. hose ends, 8 ft (2.44 m) long

Microbore hoses that provide a very quick, low volume, high pressure way of connecting to any pressure instrumentation, hand pump, calibration source or device under test

Features

- Low volume reduces the pumping effort or compressed gas usage in pressure calibration
- No thread sealant required â€" connect to adapters without wrenches, thread sealant or thread tape
- Bubble tight connections to 6900 psi (475 bar) with no moving parts reduces maintenance to almost zero
- Hose is hard to break and very flexible
- Adapt from hose to virtually any device under test with only one connection
- · Silver color dramatically reduces the effect that changing temperature has on pressure stability
- A corrosion resistant strain-relief on each hose end reduces wear and dramatically increases hose life
- Hose is pin-pricked for use in Natural Gas applications
- Made in U.S.A.

Specifications

8 ft
0 to 6900 psi (0 to 475 bar)
27000 psi (1,860 bar)
Female Quick-test, stainless steel
Female Quick-test, stainless steel
-40 to 140 °F (-40 to 60 °C)
0.2 in (5.1 mm)
0.08 in (2.0 mm)
1 in (25.4 mm)
Silver
Polyamide core tube, High tensile synthetic fiber and polyamide outer cover
Stainless Steel
Water, Petroleum Based Oil, Air, Inert Gas