

Part No.

# QTVC-1KPSIG-M

QTVC volume controller, 1000 PSI analog gauge, 6ft, 3ft hoses, (2) 1/4" MNPT process conn.

Connect to and calibrate both very low or high pressure instrumentation using included volume controller and pressure gauge

## Features

- Proprietary pressure balanced fine adjustment piston allows for extremely precise, finger-tip control of pressure at 0.03 psi (2 mbar) or 3000 psi (210 bar) or any range in between.
- Fine adjust piston, fill, balance and vent valves are in one light weight, compact unit
- Includes handle, Quick-test System<sup>®</sup>, outlet connections, hoses and adapters
- Low volume Quick-test hose, gauge adapter and process connection can be attached to QTVC without thread sealant or a wrench
- Soft-seated valves make filling and venting the system very precise
- Included stand for laboratory or table top use (QTVC-LKIT)
- Optional padded strap for field use (NPAK-STRP)
- Made in U.S.A.

## Item Includes

- Assembly - QTVC Assembly (QTVC)
- Gauge - 0-1000 psig Analog Test Gauge ( $\pm 0.5\%$  full scale accuracy) (GAUG-1000)
- Gauge Adapter - 1/4" female NPT x female Quick-test, no check-valve, brass (QTHA-2FBA)
- Hose - Quick-test 6900 psi hose, brass hose ends, 6 ft (1.83 m) long (QTQT-HOS-6ft)
- Hose - Quick-test 6900 psi hose, brass hose ends, 3 ft (92 cm) long (QTQT-HOS-3ft)
- Hose Adapter - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)
- Hose Adapter - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)

## Specifications

Pressure Range	0 to 3000 psi (0 to 207 bar)
Gauge Pressure Range	0 to 1000 psig
Vacuum Range	0 to 10" Hg (0 to 254 mmHG)
Temperature range	0 to 130 °F (-18 to 54 °C)
Gauge Temperature range	-40 to 140 °F (-40 to 60 °C)
Construction	Anodized Aluminum, Brass, Plated Steel, Stainless Steel
Seal materials	Buna-N, Delrin, Teflon



QTVC-1KPSIG-M



QTVC-1KPSIG-M

Weight	7.16 lb (3.2 kg)
Dimensions	H: 12.38 in (31.45 cm) x W: 8.5 in (21.59 cm) x D: 7.38 in (18.75 cm)