

BUILDING



ADVANCED THERMAL IMAGING

REIMAGINED FROM THE HANDLE UP

FLIR Exx-Series™
E75 | E85 | E95





BRILLIANCE AT WORK



FLIR redesigned the Exx-Series from the handle up to deliver the best performance, resolution, and sensitivity of any pistol-grip handheld thermal camera. The new Exx-Series camera is packed with the features you need to detect the early signs of water intrusion, air leaks, and other building deficiencies before they cause serious damage.

FLIR Exx-Series cameras now offer:

- Up to 161,472 points of measurement
- UltraMax® processing for 4x pixel resolution
- Our best MSX® enhancement
- Laser distance meter improves autofocus, provides distance and on-screen area measurement*
- A larger, 4" display that's 33% brighter
- A responsive new interface
- Improved organization and reporting options

*E85/E95 only



See Greater Detail

- Vibrant LCD is 33% brighter than earlier models
- Large 4" display with 160° viewing angle
- Up to 464 x 348 true native IR resolution
- Improved FLIR MSX® image enhancement

Focus Fast & True

- Laser-assisted autofocus improves accuracy for precise temperature measurements
- Continuous focus mode responds quickly, promotes safe one-hand use
- Autofocus and record functions separated to prevent accidental re-focusing

Quickly Discover Building Deficiencies

- Detects temperature differences down to 30 mK
- True 42° FOV for wide area surveys with a single lens
- Measure area (m² or ft²) of moisture intrusion or air leak on-screen*

*E85, E95 only

UNPARALLELED PERFORMANCE




The Exx-Series is packed with the high performance features you need to quickly detect and report hidden building deficiencies: superior temperature sensitivity; bright, bold on-screen imagery; razor-sharp focus; and a rapid-response user interface.

Navigate Screens Easier

- Quick response capacitive touchscreen
- Updated GUI with improved flow and feedback
- Logical navigation on screen and in menus

Document & Report Problems

- Embed moisture meter data through METERLiNK®
- Upload images and report critical issues over Wi-Fi
- Image annotation through voice, text, on-screen sketch, GPS tagging, and compass
- Enhanced image analysis and reporting through FLIR Tools+ software





FLIR Exx-Series™
E75 | E85 | E95



Laser provides distance measurement and precise autofocus

Laser pointer provides visual guidance

True 42° FOV for wide area surveys with a single lens

Bright LED work lights improve image clarity in dim areas

5 MP digital camera now closer to thermal detector for superior MSX® enhancements

Separate Autofocus and Image Recording buttons

HARD-WORKING DESIGN, FOR HARD-WORKING PROS

This sleek new design isn't just window-dressing. From the rubberized, water-tight chassis to the scratch-resistant Dragontrail™ cover glass LCD, the new Exx-Series is made to work hard all day long.



DESIGNED WITH YOU IN MIND



The Best Lenses Need the Best Autofocus

FLIR took its cue from the digital camera industry when re-engineering the Exx-Series focus system. Whether you choose autofocus or continuous focus, the camera's precise laser-assisted focus and FLIR's innovative lenses ensure you get crisp results, for the most accurate temperature readings.

Work Safer

Your job can take you up ladders and into crawl-spaces, so you need tools that can be used one-handed and worry-free. FLIR designed its new Exx-Series cameras to be tough enough to use every day, with simplified buttons and intuitive screens that allow you to focus on your work – instead of on the camera controls.

Work Smarter

The new Exx-Series cameras produce standard radiometric JPEGs that can be opened and viewed without proprietary software. Image files produced by Exx-Series cameras are supported by FLIR's Software Development Kit (ATLAS SDK), so companies can use their own software and still support read-out of thermal measurements, METERLiNK[®] data, and other important parameters embedded within the image. Current and voltage measurements embedded in image files are also accessible.

Features by Camera	E75	E85	E95
IR Resolution	320 x 240 (76,800 pixels)	384 x 288 (110,592 pixels)	464 x 348 (161,472 pixels)
UltraMax® Resolution	307,200 pixels	442,368 pixels	645,888 pixels
Object Temperature Range	-20°C to 120°C 0°C to 650°C Optional 300°C to 1000°C	-20°C to 120°C 0°C to 650°C 300°C to 1200°C	-20°C to 120°C 0°C to 650°C 300°C to 1500°C
Time-lapse (Infrared)	No	No	10 sec to 24 hours
Laser Area Measurement	No	Yes	Yes
Spotmeter	1 in live mode	3 in live mode	3 in live mode
Area	No	3 in live mode	3 in live mode
Common Features			
Exx-Series			
Detector Type and Pitch	Uncooled microbolometer, 17 µm		
Thermal Sensitivity/NETD	< 0.03°C @ 30°C		
Spectral Range	7.5 - 14.0 µm		
Image Frequency	30 Hz		
Field of View (FOV)	42° x 32° (10 mm lens), 24° x 18° (17 mm lens), 14° x 10° (29 mm lens)		
F-Number	f/1.3, f/1.1		
Lens Identification	Camera automatically identifies optional lenses without a factory calibration		
Focus	Continuous, one-shot laser distance meter (LDM), one-shot contrast, manual		
Digital Zoom	1-4x continuous		

Exx-Series cameras are backed by FLIR's industry-leading warranty

2 years: Full protection, parts, labor

10 years: Detector



*After product registration on www.flir.com

FLIR Exx-Series™

Image Presentation and Modes	
Display	4", 640 x 480 pixel touchscreen LCD with auto-rotation
Digital Camera	5 MP, 53° x 41° FOV
Color Palettes	Iron, Gray, Rainbow, Arctic, Lava, Rainbow HC
Image Modes	Infrared, visual, MSX®, Picture-in-Picture
Picture-in-Picture	Resizable and movable
MSX®	Embosses visual details on full resolution thermal image
UltraMax®	Super-resolution process quadruples pixel count, activated in FLIR Tools+
Measurement and Analysis	
Accuracy	±2°C or ±2% of reading for ambient temperature 15°C to 35°C and object temperature above 0°C
Alarms	Moisture alarm, insulation alarm, measurement alarms
Color Alarm (Isotherm)	Above/below/interval/condensation/insulation
Laser Distance Measurement	Yes, on-screen
Measurement Presets	No measurement, center spot, hot spot, cold spot, User Preset 1, User Preset 2
Image Storage	
Storage Media	Removable SD card (8 GB)
Image File Format	Standard radiometric JPEG, measurement data included
Image Annotations	
Voice	60 sec. via built-in mic or via Bluetooth
Text	Text from predefined list or touchscreen keyboard
Image Sketch	Yes, on infrared images only
Compass, GPS	Yes; automatic GPS image tagging
METERLINK®	Yes; several readings
Video Recording and Streaming	
Radiometric IR Video Recording	Real-time radiometric recording (.csq)
Non-Radiometric IR or Visual Video	H.264 to memory card
Radiometric IR Video Streaming	Yes, over UVC or Wi-Fi
Non-Radiometric IR Video Streaming	H.264 or MPEG-4 over Wi-Fi MJPEG over UVC or Wi-Fi
Communication Interfaces	USB 2.0, Bluetooth, Wi-Fi
Video Out	DisplayPort over USB Type-C
Additional Data	
Battery Type	Li-ion battery, charged in camera or on separate charger
Battery Operating Time	Approx. 2.5 hours at 25°C ambient temperature and typical use
Operating Temperature Range	-15°C to 50°C
Storage Temperature Range	-40°C to 70°C
Shock/Vibration/Encapsulation; Safety	25 g / IEC 60068-2-27, 2 g / IEC 60068-2-6, IP 54 / IEC 60529; EN/UL/CSA/PSE 60950-1
Weight/Dimensions w/o Lens	1 kg, 27.8 x 11.6 x 11.3 cm
Box Contents	Infrared camera with lens, battery (2 ea), battery charger with power supply, front lens and light protection, straps (hand and wrist), lanyards, lens caps (front and rear), lens cleaning cloth, 15 W3 A power supply, printed documentation, 8 GB SD card, Torx screwdriver, cables (USB 2.0 A to USB Type-C, USB Type-C to HDMI, USB Type-C to USB Type-C)

TECHNICAL SPECIFICATIONS



The Infrared Training Center

The greater your knowledge about thermal imaging, the greater the dividends you'll realize for your company and your career. That's why the Infrared Training Center (ITC) offers classes for practically every application, from free online courses to advanced training that can certify you as a thermography expert, qualifying you to take a leadership role in your internal IR program.

ITC classes include:

- Thermography Fundamentals Training
- IR Building Inspection
- IR Roofing Inspection

Thermography Certification Training

Level I certifies that you know how a thermal imager works and how to use it. Level II cranks your credibility up a notch with more in-depth concepts and intensive labs. Level III asserts that you have knowledge and skills to administer your company's thermography program. These certifications offer strong validation to support the work you do as a thermographer.

Mobile Training Units and on-site training at your facility are encouraged if you would like to certify a group of 10 or more. For a complete list and schedule of courses and more information, visit www.infraredtraining.com.

SWEDEN

Instruments Division
FLIR Systems AB
Antennvägen 6
187 66 Täby
Tel. : +46 (0)8 753 25 00
E-mail : flir@flir.com

Benelux

Sales Administration
FLIR Commercial Systems
Luxemburgstraat 2
2321 Meer
Belgium
Tel.: +32 (0) 3665 5100

FLIR Germany

Frankfurt
Tel. +49 (0)69 95 00 900

FLIR Italy

Milan
Tel. +39 (0)2 99 45 10 01

FLIR Spain

Madrid
Tel. +34 91 573 48 27

FLIR Middle East

Dubai
Tel. +971 4 299 6898

FLIR Africa

Johannesburg
Tel. +27 11 300 5622

FLIR France

Torcy
Tel. +33 (0)1 60 37 01 00

FLIR UK

West Malling
Tel. +44 (0)1732 220 011

FLIR Russia

Moscow
Tel. + 7 495 669 70 72

FLIR Turkey

Istanbul
Tel. +90 (212) 317 90 55

For more information:

flir@flir.com

www.flir.com
NASDAQ: FLIR

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2017 FLIR Systems, Inc. All rights reserved. [03/17] 16-1455_BLD_EMEA



The World's *Sixth Sense*®