



**RT02 ORDER CODES RT01**

**Example Order Number:**

**R5T185L483-006-00 - 4, MC** or **R5T185L483-006-01A,304 - 16** - PAGE RTD- - PAGE RTD-

**3-1 Plug and Jack Sheath Terminations**

CODE	DESCRIPTION
4 <sup>[1]</sup>	Standard plug
5 <sup>[1]</sup>	Standard jack
6 <sup>[2]</sup>	Miniature plug
7 <sup>[2]</sup>	Miniature jack
<b>Options</b>	
MC	Mating connector
CL <sup>[3]</sup>	Compression L bracket to hold plug to sheath
[1] If used with 3/8" O.D., option CL must be specified	
[2] Not available with 1/4" O.D. or 3/8" O.D. sheath	
[3] Not available with miniature connector	

**3-1 Sheath Terminations**

CODE	DESCRIPTION
22 <sup>[1]</sup>	3" individual leads with terminal pins
[1] High temp RTDs are supplied with 1" long transition	

**3-2 Leadwire transitions**

(Requires Table 4 and 5 selections)

CODE	DESCRIPTION
13 <sup>[1]</sup>	Same size transition with heat-shrink tubing 104 °C [220 °F]
15	Extension leadwire transition with relief spring 204 °C [400 °F]
16	Extension leadwire transition with heat-shrink tubing 104 °C [220 °F]
18 <sup>[1]</sup>	Same size transition without heat-shrink tubing 204 °C [400 °F]
19	Extension leadwire transition without spring or heat-shrink tubing 204 °C [400 °F]
<b>Options</b>	
HT <sup>[2]</sup>	High temperature potting 538 °C [1000 °F] not available with option 13 or 16
[1] Not available with flex armor	
[2] Not available with option 13 or 16. When specifying high temp potting with Flex Armor option 19 must be selected.	

**3-2 Threaded Fittings with Extension Leadwire**

(Requires Table 4 and 5 selections)

CODE	DESCRIPTION
6HN23	1/2" x 1/2" NPT steel hex nipple
8HN23	1/2" x 1/2" NPT stainless steel hex nipple
9HP23	1/2" NPT stainless steel bushing (no process threads)
8RNDC23	3/4" process x 1/2" NPT stainless steel hex nipple